

**ANNUAL PERFORMANCE
OF
OG-300 CERTIFIED SYSTEMS
IN
TUCSON, ARIZONA**



December 2008

Solar Rating and Certification Corporation
c/o FSEC, 1679 Clearlake Road
Cocoa, FL 32922-5703
(321) 638-1537 (321) 638-1010 Fax

SOLAR RATING AND CERTIFICATION CORPORATION

Estimated Annual Performance of OG-300 Certified Solar Water Heating Systems in Tucson, Arizona

Introduction

The Solar Rating and Certification Corporation (SRCC) is a non-profit organization whose primary purpose is the development and implementation of certification programs and national rating standards for solar energy equipment. The SRCC was incorporated in October of 1980 as an independent third-party certification entity. It is governed by a twelve-member board of Directors with representation from the public, private and generalist Sectors. It is unique in that it is the only national certification program established solely for solar energy products. It is also the only national certification organization whose programs are the direct result of combined efforts of state organizations involved in the administration of standards and an industry association.

The combined programs of the Solar Rating and Certification Corporation provide one-time certification, national recognition, product credibility, and standardized comparisons of solar energy products. The SRCC programs serve three primary constituencies: the solar energy industry, solar consumers, and state and federal regulatory bodies. All three constituencies benefit from the SRCC programs by obtaining a national state-of-the-art rating system, a mechanism to develop consumer confidence, and a rational and defensible criterion for tax credit qualification and other solar incentive programs.

The OG-300 certification program for solar water heating systems was established in 1992. It integrates results of collector tests and system tests with evaluations against minimum standards of system durability, reliability, safety and operation; as well as factors affecting total system design, installation, maintenance and service. A copy of the certification requirements¹ is available from SRCC.

Performance Estimation Procedures

SRCC uses a computer model² to estimate the thermal performance of solar water heating systems under specified conditions. A separate computer model for each system is developed from test data on some of the system components, manufacturer's literature on the others, and theoretical calculations. The SRCC rating calculated using the computer model is called the Solar Energy Factor. It is published in a Directory and in a summary booklet³. These ratings are based on conditions similar to the ones defined by the U.S. Department of Energy for testing

¹ "Operating Guidelines and Minimum Standards for Certifying Solar Water Heating Systems", April 1997.

² "TRNSYS A Transient Simulation Program", Solar Energy Laboratory, University of Wisconsin - Madison, July 1994.

³ "Directory of SRCC Certified Solar Collector and Water Heating System Ratings" and the Summary are available from SRCC.

conventional water heaters. These conditions describe hot water usage for a single day. Keep in mind that these ratings are only estimates based on an assumed set of operating conditions and that your actual performance will vary depending your hot water usage pattern and actual weather conditions.

The estimated annual performance indicators given in the attached tables are different from the SRCC ratings and are not directly comparable. The annual performance listed in this booklet was developed to provide an estimate of how solar water heaters could perform over a whole year in a specific location. The SRCC rating estimates the performance of the systems under “rating” conditions. Once again, keep in mind that these ratings are only estimates.

Operating Conditions

The estimated annual performance listed in the attached tables is based on the following conditions:

Condition	Value
Hot water load	64.3 gallons (243 liters) per day drawn throughout the day with the maximum loads occurring at 8 am and 8 pm ⁴ .
Water mains temperature	Varied monthly using Tucson, AZ values ⁵ .
Collector orientation	Facing south at a tilt of 23°.
Distance from collector to tank	25 feet (7.6 meters) pipe length (each way), 16 feet (4.9 meters) vertical rise.
Backup heater set point	125°F (51.7°C) ⁶
Weather conditions	TMY2 data for Tucson, AZ ⁷
Air temperature around indoor tanks	$T_{air} + [(72 - T_{air})/3]$, this estimates the temperature in a garage.

For reference, a conventional 50 gallon electric water heater with an energy factor of 0.9 would consume 3,600 kilowatt hours (kWh) per year under these conditions and a 50 gallon gas water heater with an energy factor of 0.6 would consume 185 therms (including delivered energy and losses).

Table Entries

The tables give the estimated annual performance for all OG-300 certified solar water heating systems. There are separate tables for systems using electric and gas backup water heaters. The

⁴ This profile adapted from the 1995 ASHRAE Applications Handbook, Chapter 45, and “A Domestic Hot Water Use Database”, Becker and Stogsdill, ASHRAE Journal, September 1990.

⁵ “F-Chart”, Klein and Beckman, F-Chart Software, 1993.

⁶ This set point was chosen as a compromise between the Department of Energy recommendation of 125°F (51.7°C), the plumbing code 120°F (48.9°C) maximum allowable in showers and tubs, and the 135°F (57.2°C) used in the Department of Energy test for conventional water heaters.

⁷ “TMY2s, Typical Meteorological Years”, National Renewable Energy Laboratory, June 1995.

systems are listed by company name, system name and model number. The remaining columns are as follows:

System Number: SRCC's reference number. This number is used to cross-reference a specific system in the Directory.

FTL: This is the Freeze Tolerance Limit. The Freeze Tolerance Limit is the temperature below which the solar water heating system might suffer damage due to freezing. This means that if the outdoor air temperature drops near the freeze tolerance limit it is necessary to follow the instructions in the owner's manual for protecting the system.

Energy Savings: This is the estimated annual performance of the system. This value is the quantity of energy that did not have to be provided by electricity or gas because of the contribution of the solar water heating system. Note that the electricity required to operate any pumps and controllers used in a particular system has been accounted for.

Comments: This column lists additional information regarding specific systems.

Solar Rating and Certification Corporation
Estimated Annual Performance of OG-300 Certified Solar Water Heating Systems
Tucson, Arizona
with Electric Backup

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
ACR Solar International					
Skyline System 3	100133C50	1999003G	30	2600	
Skyline System 3	200131C50	1999003A	30	2100	
Skyline System 3	200132C50	1999003B	30	3000	
Skyline System 3	200132C502TE	2002002A	30	2800	
Skyline System 3	200132C50T20E	2002004A	20	2700	
Skyline System 3	200132C80	1999003F	30	3100	
Skyline System 3	200133C50	1999003D	30	3300	
Skyline System 3	200133C80	1999003C	30	3400	
Skyline System 5	200152C80EX	2000007A	-54	2700	
Skyline System 5	200152C80EX2TE	2002003A	-54	2500	
Skyline System 5	200153C80EX	2000007B	-54	3100	
Skyline System 5	200153C80EX2TE	2002003B	-54	3000	
Skyline System 5	200154C80EX	2000007C	-54	3300	
Alternate Energy Technologies					
EagleSun	DB-120-64	2006006E	-20	3000	
EagleSun	DB-120-80	2006006F	-20	3100	
EagleSun	DB-120-96	2006006G	-20	3200	
EagleSun	DB-80-40	2006006A	-20	2500	
EagleSun	DB-80-52	2006006B	-20	2800	
EagleSun	DB-80-64	2006006C	-20	2900	
EagleSun	DB-80-80	2006006D	-20	3000	
EagleSun DX	DX-120-64	2006007E	-20	3200	
EagleSun DX	DX-120-80	2006007F	-20	3300	
EagleSun DX	DX-120-96	2006007G	-20	3300	
EagleSun DX	DX-80-40	2006007A	-20	2900	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
EagleSun DX	DX-80-52	2006007B	-20	3000	
EagleSun DX	DX-80-64	2006007C	-20	3200	
EagleSun DX	DX-80-80	2006007D	-20	3200	
Bobcat & Sun, Inc.					
Sun-Pak	SP32CHE	1994005E	-60	2100	
Sun-Pak	SP32CHE-1	1994004E	-60	2400	
Sun-Pak	SP32PHE	1994005A	-60	2000	
Sun-Pak	SP32PHE-1	1994004A	-60	2300	
Sun-Pak	SP40CHE	1994005G	-60	2400	
Sun-Pak	SP40CHE-1	1994004G	-60	2600	
Sun-Pak	SP40PHE	1994005C	-60	2300	
Sun-Pak	SP40PHE-1	1994004C	-60	2500	
Sun-Pak	SP64CHE	1994005F	-60	2900	
Sun-Pak	SP64CHE-1	1994004F	-60	3000	
Sun-Pak	SP64PHE	1994005B	-60	2800	
Sun-Pak	SP64PHE-1	1994004B	-60	2900	
Sun-Pak	SP80CHE	1994005H	-60	3000	
Sun-Pak	SP80CHE-1	1994004H	-60	3100	
Sun-Pak	SP80PHE	1994005D	-60	3000	
Sun-Pak	SP80PHE-1	1994004D	-60	3000	
BTF, Ltd.					
Solar Patriot TM	SP20-1-65G-PV-E	2006018A	-50	1800	
Solar Patriot TM	SP20-2-80G-PV-E	2006018B	-50	2700	
Butler Sun Solutions					
Solar Butler	BSS-PV1-40Ea	2005005A	-54	2400	
Solar Butler	BSS-PV1-40Eb	2005005B	-54	1500	
Solar Butler	BSS-PV1-40Ec	2005005I	-54	2100	
Solar Butler	BSS-PV1-40Ed	2005005J	-54	2200	
Solar Butler	BSS-PV1-50Ea	2005005C	-54	2200	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Solar Butler	BSS-PV1-50Ec	2005005H	-54	2100	
Solar Butler	BSS-PV1-80E2a	2005008A	-54	2300	
Solar Butler	BSS-PV1-80E2b	2005008B	-54	2700	
Solar Butler	BSS-PV1-80Ea	2005005E	-54	2900	
Solar Butler	BSS-PV1-80Ec	2005005G	-54	2600	
Solar Butler	BSS-S1-40Ea	2003001A	-54	1800	
Solar Butler	BSS-S1-40Eb	2003001B	-54	1500	
Solar Butler	BSS-S1-40Ec	2003001I	-54	2100	
Solar Butler	BSS-S1-50Ea	2003001C	-54	2200	
Solar Butler	BSS-S1-50Ec	2003001H	-54	2100	
Solar Butler	BSS-S1-80E2a	2005007A	-54	2300	
Solar Butler	BSS-S1-80E2b	2005007B	-54	2600	
Solar Butler	BSS-S1-80Ea	2003001E	-54	2900	
Solar Butler	BSS-S1-80Ec	2003001G	-54	2600	

Davis Energy Group

SunCache	SCG-100-ES	2007007B	20	1600	
SunCache	SCG-50-ES	2007007A	20	1400	
SunCache	SCU-50-ES	2004007A	20	900	

Energy Laboratories, Inc.

Duro-Drainback Solar Water Heat	D2B-12009120	2004011E	-20	3300	
Duro-Drainback Solar Water Heat	D2B-12009-128	2004011F	-20	3300	
Duro-Drainback Solar Water Heat	D2B-12009-40	2004011A	-20	2700	
Duro-Drainback Solar Water Heat	D2B-12009-64	2004011B	-20	3100	
Duro-Drainback Solar Water Heat	D2B-12009-80	2004011C	-20	3200	
Duro-Drainback Solar Water Heat	D2B-12009-96	2004011D	-20	3200	
Duro-Drainback Solar Water Heat	D2B-8009-32	2004010A	-20	2300	
Duro-Drainback Solar Water Heat	D2B-8009-40	2004010B	-20	2600	
Duro-Drainback Solar Water Heat	D2B-8009-42	2004010C	-20	2700	
Duro-Drainback Solar Water Heat	D2B-8009-63	2004010D	-20	3000	
Duro-Drainback Solar Water Heat	D2B-8009-64	2004010E	-20	3000	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Duro-Drainback Solar Water Heat	D2B-8009-80	2004010F	-20	3100	
Roof Integrated Thermosiphon Sy	RITH 72 E	2004006A	22	2800	
Enerworks, Inc.					
Single Tank Solar Water Heating	EWRA1-E120-1T	2007010F	-50	2900	
Single Tank Solar Water Heating	EWRA1-E80-1T	2007010A	-50	2900	
Single Tank Solar Water Heating	EWRA2-E120-1T	2007010C	-50	3400	
Single Tank Solar Water Heating	EWRA2-E80-1T	2007010B	-50	3400	
Single Tank Solar Water Heating	EWRA3-E120-1T	2007010D	-50	3500	
Single Tank Solar Water Heating	EWRA4-E120-1T	2007010E	-50	3500	
Solar Water Heating Appliance	EWRA1-E40	2005012A	-50	2600	
Solar Water Heating Appliance	EWRA1-E80	2005012B	-50	2600	
Solar Water Heating Appliance	EWRA2-E100	2005012D	-50	3100	
Solar Water Heating Appliance	EWRA2-E80	2005012C	-50	3200	
Solar Water Heating Appliance	EWRA3-E100	2005012E	-50	2800	
Solar Water Heating Appliance	EWRA3-E120	2005012F	-50	2900	
Solar Water Heating Appliance	EWRA4-E120	2005012G	-50	2800	
Solar Water Heating Appliance	EWRA4-E144	2005012H	-50	2800	
Fafco, Inc.					
Polymer Drainback	VDB-48U-50E	2007002A	-20	2100	
Polymer Drainback	VDB-48U-50E-50S	2007003A	-20	1900	
Polymer Drainback	VDB-48U-50E-80S	2007003B	-20	2000	
Polymer Drainback	VDB-48U-80E	2007002B	-20	2700	
Polymer Drainback	VDB-48UX2-50E	2007002C	-20	2400	
Polymer Drainback	VDB-48UX2-50E-50S	2007003C	-20	2200	
Polymer Drainback	VDB-48UX2-50E-80S	2007003D	-20	2400	
Polymer Drainback	VDB-48UX2-80E	2007002D	-20	2700	
Heat Transfer Products					
SuperStor Conntender Solar	SSC-119SE	2007011C	-60	3200	
SuperStor Contender Solar	SSC-50SE	2007011A	-60	2500	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SuperStor Contender Solar	SSC-80SE	2007011B	-60	2800	
SuperStor Ultra Solar	SSU-119SE	2007019C	-60	3100	
SuperStor Ultra Solar	SSU119SE-DW	2007020B	-60	3200	
SuperStor Ultra Solar	SSU-60SE	2007019A	-60	2400	
SuperStor Ultra Solar	SSU-80SE	2007019B	-60	2800	
SuperStor Ultra Solar	SSU80SE-DW	2007020A	-60	2800	

Heliodyne, Inc.

Helio-Flo	HF 1408 G 80 AC S E	2001023A	27	3100	
Helio-Flo	HF 1410 G 120 AC S E	2001023C	27	3400	
Helio-Flo	HF 1410 G 80 AC D E	2001024A	27	3200	
Helio-Flo	HF 1410 G 80 AC S E	2001023B	27	3300	
Helio-Flo	HF 23366 G 80 AC D E	2001024B	27	3400	
Helio-Flo	HF 23366 G 80 AC S E	2001023D	27	3400	
Helio-Flo	HF 2408 G 120 AC D E	2001024D	27	3500	
Helio-Flo	HF 2408 G 120 AC S E	2001023F	27	3500	
Helio-Flo	HF 2408 G 80 AC D E	2001024C	27	3400	
Helio-Flo	HF 2408 G 80 AC S E	2001023E	27	3500	
Helio-Flo	HF 2410 G 120 AC D E	2001024E	27	3500	
Helio-Flo	HF 2410 G 120 AC S E	2001023G	27	3500	
Helio-Flo	HF 3408 G 120 AC D E	2001024F	27	3400	
Helio-Flo	HF 3408 G 120 AC S E	2001023H	27	3400	
Helio-Flo	HF 3410 G 120 AC D E	2001024G	27	3400	
Helio-Flo	HF 3410 G 160 AC S E	2001023I	27	3400	
Heliopak	16 DWCL HP 1 3366 G 50 ACS	1992010J	-60	2600	
Heliopak	16 DWCL HP 1 3366 G 80 ACD	1992013G	-60	2300	
Heliopak	16 DWCL HP 1 3366 G 80 ACS	1992010K	-60	2600	
Heliopak	16 DWCL HP 1 408 G 65 ACD	1992013F	-60	2600	
Heliopak	16 DWCL HP 1 408 G 65 ACS	1992010A	-60	2800	
Heliopak	16 DWCL HP 1 408 G 65 PVD	1996004C	-60	2900	
Heliopak	16 DWCL HP 1 408 G 65 PVS	1996003C	-60	3100	
Heliopak	16 DWCL HP 1 408 G 80 ACD	1992013I	-60	2600	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
 SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Heliopak	16 DWCL HP 1 408 G 80 ACS	1992010N	-60	2800	
Heliopak	16 DWCL HP 1 410 G 65 ACD	1992013A	-60	2800	
Heliopak	16 DWCL HP 1 410 G 80 ACD	1992013J	-60	2900	
Heliopak	16 DWCL HP 1 410 G 80 ACS	1992010B	-60	3000	
Heliopak	16 DWCL HP 1 410 G 80 PVD	1996004A	-60	3200	
Heliopak	16 DWCL HP 1 410 G 80 PVS	1996003A	-60	3300	
Heliopak	16 DWCL HP 2 3366 G 120 ACS	1992010M	-60	3200	
Heliopak	16 DWCL HP 2 3366 G 80 ACD	1992013H	-60	3100	
Heliopak	16 DWCL HP 2 3366 G 80 ACS	1992010L	-60	3200	
Heliopak	16 DWCL HP 2 408 G 120 ACD	1992013C	-60	3200	
Heliopak	16 DWCL HP 2 408 G 120 ACS	1992010C	-60	3200	
Heliopak	16 DWCL HP 2 408 G 80 ACD	1992013B	-60	3200	
Heliopak	16 DWCL HP 2 410 G 120 ACD	1992013D	-60	3200	
Heliopak	16 DWCL HP 2 410 G 120 ACS	1992010O	-60	3300	
Heliopak	DWCL HE HP 1 3366 G 80 ACS	1992010I	-60	2500	
Heliopak	DWCL HE HP 1 408 G 80 ACS	1992010D	-60	2800	
Heliopak	DWCL HE HP 1 410 G 80 ACS	1992010E	-60	3000	
Helio-Pak Helix SS PV	HP HX SS 1 3366 G PV 50 EE S	2005003A	-60	2700	
Helio-Pak Helix SS PV	HP HX SS 1 3366 G PV 65 EE S	2005003B	-60	2700	
Helio-Pak Helix SS PV	HP HX SS 1 408 G PV 50 EE S	2005003C	-60	2900	
Helio-Pak Helix SS PV	HP HX SS 1 408 G PV 65 EE S	2005003D	-60	3000	
Helio-Pak Helix SS PV	HP HX SS 1 408 G PV 80 EE S	2005003E	-60	3000	
Helio-Pak Helix SS PV	HP HX SS 1 410 G PV 65 EE S	2005003F	-60	3200	
Helio-Pak Helix SS PV	HP HX SS 1 410 G PV 80 EE S	2005003G	-60	3200	
Helio-Pak Helix SS PV	HP HX SS 2 3366 G PV 80 EE S	2005003H	-60	3400	
Helio-Pak Helix SS PV	HP HX SS 2 408 G PV 120 SE S	2005003I	-60	3500	
Helio-Pak Helix SS PV	HP HX SS 2 410 G PV 120 SE S	2005003J	-60	3600	
Helio-Pak Helix SS PV	HP HX SS 3 3366 G PV 120 SE S	2005003K	-60	3600	
Helio-Pak Helix SS PV	HP HX SS 3 408 G PV 120 SE S	2005003L	-60	3600	
HP HELIX AC	HP 1 408 GAC WAC 50 S	1999004A	-60	2700	
HP HELIX AC	HP 1 410 GAC WAC 80 S	1999004B	-60	3100	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Integrated Solar, LLC					
CopperSun	CS330-E	1997001B	20	1700	
CopperSun	CS330SV-E	2002007A	20	1500	
CopperSun	CS340-E	1997001C	20	1700	
CopperSun	CS340SV-E	2002007B	20	1500	
CopperSun	CS440-E	1997001A	20	1900	
CopperSun	CS450-E	1997001D	20	2000	
Radco Drainback Heat Exchanger	R-DBHX-12-120-D-80P	1992007I	-60	2900	
Radco Drainback Heat Exchanger	R-DBHX-8-120S-80P	1994007C	-60	3100	
Radco Drainback Heat Exchanger	R-DBHX-8-65-D-40P	1992007A	-60	2300	
Radco Drainback Heat Exchanger	R-DBHX-8-65S-40P	1994007A	-60	2500	
Radco Drainback Heat Exchanger	R-DBHX-8-80-D-64P	1992007C	-60	2800	
Radco Drainback Heat Exchanger	R-DBHX-8-80S-40C	1994007E	-60	2800	
Radco Drainback Heat Exchanger	R-DBHX-8-80S-40P	1994007D	-60	2600	
Radco Drainback Heat Exchanger	R-DBHX-8-80S-48C	1994007F	-60	2900	
Radco Drainback Heat Exchanger	R-DBHX-8-80S-48P	1994007G	-60	2700	
Radco Drainback Heat Exchanger	R-DBHX-8-80S-64P	1994007B	-60	2900	
Morley Manufacturing					
High Sierra Drainback	HS60B/40	1992014A	-60	2700	
Mr. Sun Solar					
Sol-Reliant	SR 40/80 E PVDB	2004008B	-50	3100	
Sol-Reliant	SR 56/120 SE PVDB	2007015A	-50	3500	
Sol-Reliant	SR 56/80 E PVDB	2004008A	-50	3400	
Sol-Reliant	SR112/120 E PVDB	2007025C	-50	3600	
Sol-Reliant	SR112/80 E PVDB	2007025B	-50	3600	
Sol-Reliant	SR80/80 E PVDB	2007025A	-50	3500	
Pacific West Solar					
Freeze Safe SWH	FS410-80-1	2008001A	-9	2900	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Power Partners, Inc.					
System 3	100133C50	2008002G	30	2600	
System 3	200131C50	2008002A	30	2100	
System 3	200132C50	2008002B	30	3000	
System 3	200132C502TE	2008004A	30	2800	
System 3	200132C50T20E	2008006A	20	2700	
System 3	200132C80	2008002F	30	3100	
System 3	200133C50	2008002D	30	3300	
System 3	200133C80	2008002C	30	3400	
System 5	200152C80EX	2008003A	-54	2700	
System 5	200152C80EX2TE	2008005A	-54	2500	
System 5	200153C80EX	2008003B	-54	3100	
System 5	200153C80EX2TE	2008005B	-54	3000	
System 5	200154C80EX	2008003C	-54	3300	
Rheem Water Heaters					
Rheem Solaraide	RS47-21BP	2005013A	19	1800	
Rheem Solaraide	RS80-42BP	2005013B	19	2600	
Schuco USA L.P.					
Premium Package	Premium II-120E	2006012C	-40	3100	
Premium Package	Premium II-80E	2006012A	-40	3000	
Premium Package	Premium III-120E	2006012B	-40	3300	
Slimline Package	Slimline II-120E	2006014C	-40	3000	
Slimline Package	Slimline II-80E	2006014A	-40	3000	
Slimline Package	Slimline III-120E	2006014B	-40	3200	
Solahart Industries					
SOLAHART	181BCXII	2001011B	19	1900	
SOLAHART	181J & 181J Free Heat	2001010A	19	1800	
SOLAHART	181KF & 181KF Free Heat	2001011A	19	2000	
SOLAHART	181L	2001009A	41	1800	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SOLAHART	182BCXII	2001011D	19	2800	
SOLAHART	182J & 182J Free Heat	2001010B	19	2600	
SOLAHART	182KF & 182KF Free Heat	2001011C	19	2800	
SOLAHART	302BCXII	2001011F	19	2800	
SOLAHART	302J & 302J Free Heat	2001010C	19	2600	
SOLAHART	302JXII	2001010D	19	2600	
SOLAHART	302KF & 302KF Free Heat	2001011E	19	2800	
SOLAHART	302L	2001009B	41	2600	
SOLAHART	303BCXII	2001011H	19	3100	
SOLAHART	303J & 303J Free Heat	2001010E	19	2900	
SOLAHART	303JXII	2001010F	19	2900	
SOLAHART	303KF & 303KF Free Heat	2001011G	19	3100	
SOLAHART	303L	2001009C	41	2900	
SOLAHART	443BCXII	2001011J	19	3100	
SOLAHART	443J & 443J Free Heat	2001010G	19	2900	
SOLAHART	443JXII	2001010H	19	2900	
SOLAHART	443KF & 443KF Free Heat	2001011I	19	3100	
SOLAHART	443L	2001009D	41	2900	
SOLAHART	444BCXII	2001011L	19	3300	
SOLAHART	444J & 444J Free Heat	2001010I	19	3100	
SOLAHART	444JXII	2001010J	19	3100	
SOLAHART	444KF & 444KF Free Heat	2001011K	19	3300	
SOLAHART	444L	2001009E	41	3000	
SOLAHART	ASE 181BCXII	2001014B	19	2100	
SOLAHART	ASE 181J & ASE 181J Free Heat	2001013A	19	2000	
SOLAHART	ASE 181KF & ASE 181KF Free He	2001014A	19	2100	
SOLAHART	ASE 181L	2001012A	41	1900	
SOLAHART	ASE 182BCXII	2001014D	19	2900	
SOLAHART	ASE 182J & ASE 182J Free Heat	2001013B	19	2700	
SOLAHART	ASE 182KF & ASE 182KF Free He	2001014C	19	2900	
SOLAHART	ASE 302BCXII	2001014F	19	2900	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SOLAHART	ASE 302J & ASE 302J Free Heat	2001013C	19	2700	
SOLAHART	ASE 302JXII	2001013D	19	2700	
SOLAHART	ASE 302KF & ASE 302KF Free He	2001014E	19	2900	
SOLAHART	ASE 302L	2001012B	41	2600	
SOLAHART	ASE 303BCXII	2001014H	19	3200	
SOLAHART	ASE 303J & ASE 303J Free Heat	2001013E	19	3000	
SOLAHART	ASE 303JXII	2001013F	19	3000	
SOLAHART	ASE 303KF & ASE 303KF Free He	2001014G	19	3200	
SOLAHART	ASE 303L	2001012C	41	2900	
SOLAHART	ASE 443BCXII	2001014J	19	3200	
SOLAHART	ASE 443J & ASE 443J Free Heat	2001013G	19	3000	
SOLAHART	ASE 443JXII	2001013H	19	3000	
SOLAHART	ASE 443KF & ASE 443KF Free He	2001014I	19	3200	
SOLAHART	ASE 443L	2001012D	41	2900	
SOLAHART	ASE 444BCXII	2001014L	19	3300	
SOLAHART	ASE 444J & ASE 444J Free Heat	2001013I	19	3100	
SOLAHART	ASE 444JXII	2001013J	19	3100	
SOLAHART	ASE 444KF & ASE 444KF Free He	2001014K	19	3300	
SOLAHART	ASE 444L	2001012E	41	3000	
Streamline Electric	270SL-2Bt	2004012A	41	3100	
Streamline Electric	270SL-2L	2004012B	41	2700	
Streamline Electric	270SL-3Bt	2004012C	41	3300	
Streamline Electric	270SL-3L	2004012D	41	3000	
Streamline Electric	340SL-2Bt	2004012E	41	3100	
Streamline Electric	340SL-2L	2004012F	41	2700	
Streamline Electric	340SL-3Bt	2004012G	41	3300	
Streamline Electric	340SL-3L	2004012H	41	3000	
Streamline Electric	430SL-2Bt	2004012I	41	3100	
Streamline Electric	430SL-2L	2004012J	41	2700	
Streamline Electric	430SL-3Bt	2004012K	41	3300	
Streamline Electric	430SL-3L	2004012L	41	3000	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Solarhot					
Solvelox DB	S-SV-DB100	2007008A	-10	3100	
Solvelox DB	S-SV-DB100P32	2007008C	-10	2300	
Solvelox DB	S-SV-DB100P64	2007008B	-10	3000	
Solvelox DB	S-SV-DBET30	2007008D	-10	2800	
Solvelox DB	S-SV-DBET30-120	2007008F	-10	2800	
Solvelox DB	S-SV-DBET60	2007008E	-10	3200	
Solvelox DB	S-SV-DBET60-120	2007008G	-10	3200	
Solvelox Glycol	S-SV-G100	2007018A	-30	3100	
Solvelox Glycol	S-SV-G100ET	2007018B	-30	3200	
Solvelox Glycol	S-SV-G2ASW52B120	2007018H	-30	2900	
Solvelox Glycol	S-SV-GASWS52B80	2007018G	-30	1800	
Solvelox Glycol	S-SV-GC100P64	2007018D	-30	3000	
Solvelox Glycol	S-SV-GET30	2007018C	-30	2800	
Solvelox Glycol	S-SV-GET30-120	2007018F	-30	2900	
Solvelox Glycol	S-SV-GET60-120	2007018E	-30	3200	
Solene					
Solene/Chromagen DC Closed Lo	SLCR32DC-80HE	2006003A	-10	2600	
Solene/Chromagen DC Closed Lo	SLCR32DC-80HE-XE	2006031A	-10	2400	
Solene/Chromagen DC Closed Lo	SLCR40DC-80HE	2006003B	-10	2900	
Solene/Chromagen DC Closed Lo	SLCR40DC-80HE-XE	2006031B	-10	2700	
Solene/Chromagen DC Closed Lo	SLCR60DC-80HE	2006003E	-10	3200	
Solene/Chromagen DC Closed Lo	SLCR64DC-120HE	2006003F	-10	3200	
Solene/Chromagen DC Closed Lo	SLCR64DC-120HE-XE	2006031E	-10	3100	
Solene/Chromagen DC Closed Lo	SLCR64DC-80HE	2006003C	-10	3200	
Solene/Chromagen DC Closed Lo	SLCR64DC-80HE-XE	2006031C	-10	3100	
Solene/Chromagen DC Closed Lo	SLCR80DC-120HE	2006003G	-10	3300	
Solene/Chromagen DC Closed Lo	SLCR80DC-120HE-XE	2006031F	-10	3200	
Solene/Chromagen DC Closed Lo	SLCR80DC-80HE	2006003D	-10	3300	
Solene/Chromagen DC Closed Lo	SLCR80DC-80HE-XE	2006031D	-10	3200	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
 SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Solene/Chromagen DC Open Loo	SLCR32DC-66	2005011A	20	3000	
Solene/Chromagen DC Open Loo	SLCR40DC-80	2005011B	20	3200	
Solene/Chromagen DC Open Loo	SLCR60DC-80	2005011C	20	3400	
Solene/Chromagen DC Open Loo	SLCR64DC-120	2005011D	20	3400	
Solene/Chromagen DC Open Loo	SLCR80DC-120	2005011E	20	3500	
Solene/Chromagen Drain Back	SLCR32DC-80DB	2006001A	-10	2500	
Solene/Chromagen Drain Back	SLCR32DC-80DB-XE	2006030A	-10	2300	
Solene/Chromagen Drain Back	SLCR40DC-80DB	2006001B	-10	2800	
Solene/Chromagen Drain Back	SLCR40DC-80DB-XE	2006030B	-10	2600	
Solene/Chromagen Drain Back	SLCR60DC-80DB	2006001E	-10	3100	
Solene/Chromagen Drain Back	SLCR64DC-120DB	2006001F	-10	3100	
Solene/Chromagen Drain Back	SLCR64DC-120DB-XE	2006030E	-10	3000	
Solene/Chromagen Drain Back	SLCR64DC-80DB	2006001C	-10	3200	
Solene/Chromagen Drain Back	SLCR64DC-80DB-XE	2006030C	-10	3100	
Solene/Chromagen Drain Back	SLCR80DC-120DB	2006001G	-10	3200	
Solene/Chromagen Drain Back	SLCR80DC-120DB-XE	2006030F	-10	3200	
Solene/Chromagen Drain Back	SLCR80DC-80DB	2006001D	-10	3300	
Solene/Chromagen Drain Back	SLCR80DC-80DB-XE	2006030D	-10	3200	
Solene/Chromagen PV Open Loo	SLCR32PV-66	2006002A	20	3300	
Solene/Chromagen PV Open Loo	SLCR40PV-80	2006002B	20	3400	
Solene/Chromagen PV Open Loo	SLCR60PV-80	2006002C	20	3600	
Solene/Chromagen PV Open Loo	SLCR64PV-120	2006002D	20	3600	
Solene/Chromagen PV Open Loo	SLCR80PV-120	2006002E	20	3600	
Solene/Corona DC Closed Loop	SLCO32DC-80HE	2006023A	-10	2600	
Solene/Corona DC Closed Loop	SLCO32DC-80HE-XE	2006029A	-10	2300	
Solene/Corona DC Closed Loop	SLCO40DC-80HE	2006023B	-10	2800	
Solene/Corona DC Closed Loop	SLCO40DC-80HE-XE	2006029B	-10	2600	
Solene/Corona DC Closed Loop	SLCO60DC-80HE	2006023C	-10	3000	
Solene/Corona DC Closed Loop	SLCO64DC-120HE	2006023F	-10	3200	
Solene/Corona DC Closed Loop	SLCO64DC-120HE-XE	2006029E	-10	3100	
Solene/Corona DC Closed Loop	SLCO64DC-80HE	2006023D	-10	3200	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Solene/Corona DC Closed Loop	SLCO64DC-80HE-XE	2006029C	-10	3100	
Solene/Corona DC Closed Loop	SLCO80DC-120HE	2006023G	-10	3300	
Solene/Corona DC Closed Loop	SLCO80DC-120HE-XE	2006029F	-10	3200	
Solene/Corona DC Closed Loop	SLCO80DC-80HE	2006023E	-10	3300	
Solene/Corona DC Closed Loop	SLCO80DC-80HE-XE	2006029D	-10	3200	
Solene/Corona DC Open Loop	SLCO32DC-66	2006021A	20	3000	
Solene/Corona DC Open Loop	SLCO40DC-80	2006021B	20	3200	
Solene/Corona DC Open Loop	SLCO60DC-80	2006021C	20	3300	
Solene/Corona DC Open Loop	SLCO64DC-120	2006021D	20	3400	
Solene/Corona DC Open Loop	SLCO80DC-120	2006021E	20	3500	
Solene/Corona Drainback	SLCO32DC-80DB	2006022A	-10	2500	
Solene/Corona Drainback	SLCO32DC-80DB-XE	2006028A	-10	2200	
Solene/Corona Drainback	SLCO40DC-80DB	2006022B	-10	2800	
Solene/Corona Drainback	SLCO40DC-80DB-XE	2006028B	-10	2600	
Solene/Corona Drainback	SLCO60DC-80DB	2006022C	-10	3000	
Solene/Corona Drainback	SLCO64DC-120DB	2006022F	-10	3100	
Solene/Corona Drainback	SLCO64DC-120DB-XE	2006028E	-10	3000	
Solene/Corona Drainback	SLCO64DC-80DB	2006022D	-10	3200	
Solene/Corona Drainback	SLCO64DC-80DB-XE	2006028C	-10	3100	
Solene/Corona Drainback	SLCO80DC-120DB	2006022G	-10	3200	
Solene/Corona Drainback	SLCO80DC-120DB-XE	2006028F	-10	3200	
Solene/Corona Drainback	SLCO80DC-80DB	2006022E	-10	3300	
Solene/Corona Drainback	SLCO80DC-80DB-XE	2006028D	-10	3200	
Solene/Corona PV Open Loop	SLCO32PV-66	2006020A	20	3200	
Solene/Corona PV Open Loop	SLCO40PV-80	2006020B	20	3400	
Solene/Corona PV Open Loop	SLCO60PV-80	2006020C	20	3500	
Solene/Corona PV Open Loop	SLCO64PV-120	2006020D	20	3600	
Solene/Corona PV Open Loop	SLCO80PV-120	2006020E	20	3600	

Stitt Energy Systems, Inc.

Sup.plen.ergy Solar Water Heater	SESI-120-80	2006008B	-40	3200	
Sup.plen.ergy Solar Water Heater	SESI-80-40	2006008A	-40	2600	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SunEarth, Inc.					
Cascade	ECRD-40-80	2001026B	-50	2800	
Cascade	ECRD-40-80-2	2001027B	-50	2600	
Cascade	ECRD-48-80	2001026F	-50	2900	
Cascade	ECRD-48-80-2	2001027F	-50	2800	
Cascade	ECRD-64-80	2001026H	-50	3100	
Cascade	ECRD-64-80-2	2001027H	-50	3000	
Cascade	EPRD-40-80	2001026A	-50	2800	
Cascade	EPRD-40-80-2	2001027A	-50	2500	
Cascade	EPRD-42-80	2001026C	-50	2800	
Cascade	EPRD-42-80-2	2001027C	-50	2600	
Cascade	EPRD-48-80	2001026E	-50	2900	
Cascade	EPRD-48-80-2	2001027E	-50	2700	
Cascade	EPRD-64-80	2001026G	-50	3100	
Cascade	EPRD-64-80-2	2001027G	-50	3000	
CopperHeart	CP-20	1992011I	20	1500	
CopperHeart	CP-30	1992011E	20	2000	
CopperHeart	CP-40	1992011F	20	2200	
CopperHeart	CP-60P	1992011G	20	2500	
CopperHeart	CP-80P	1992011J	20	2700	
SOLARAY	TE32C-80-1	1993001B	-60	2900	
SOLARAY	TE32C-80-2	1996001B	-60	2800	
SOLARAY	TE32P-80-1	1993001A	-60	2800	
SOLARAY	TE32P-80-2	1996001A	-60	2700	
SOLARAY	TE40C-120-1	1993001M	-60	3100	
SOLARAY	TE40C-120-2	1996001K	-60	3000	
SOLARAY	TE40C-120-2-PV	2000003I	-60	3000	
SOLARAY	TE40C-120-PV	2000004I	-60	3200	
SOLARAY	TE40C-80-1	1993001D	-60	3100	
SOLARAY	TE40C-80-2	1996001D	-60	3000	
SOLARAY	TE40C-80-2-PV	2000003A	-60	3100	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SOLARAY	TE40C-80-PV	2000004A	-60	3200	
SOLARAY	TE40P-120-1	1993001T	-60	3000	
SOLARAY	TE40P-80-1	1993001C	-60	3100	
SOLARAY	TE40P-80-2	1996001C	-60	3000	
SOLARAY	TE40P-80-2-PV	2000003D	-60	3000	
SOLARAY	TE40P-80-PV	2000004D	-60	3100	
SOLARAY	TE48C-120-1	1993001O	-60	3200	
SOLARAY	TE48C-120-2	1996001M	-60	3100	
SOLARAY	TE48C-120-2-PV	2000003K	-60	3200	
SOLARAY	TE48C-120-PV	2000004K	-60	3300	
SOLARAY	TE48C-80-1	1993001L	-60	3200	
SOLARAY	TE48C-80-2	1996001J	-60	3200	
SOLARAY	TE48C-80-2-PV	2000003H	-60	3200	
SOLARAY	TE48C-80-PV	2000004H	-60	3300	
SOLARAY	TE48P-120-1	1993001N	-60	3200	
SOLARAY	TE48P-120-2	1996001L	-60	3100	
SOLARAY	TE48P-120-2-PV	2000003J	-60	3100	
SOLARAY	TE48P-120-PV	2000004J	-60	3300	
SOLARAY	TE48P-80-1	1993001K	-60	3200	
SOLARAY	TE48P-80-2	1996001I	-60	3100	
SOLARAY	TE48P-80-2-PV	2000003G	-60	3200	
SOLARAY	TE48P-80-PV	2000004G	-60	3300	
SOLARAY	TE64C-120-1	1993001Q	-60	3400	
SOLARAY	TE64C-120-2	1996001O	-60	3300	
SOLARAY	TE64C-120-2-PV	2000003M	-60	3400	
SOLARAY	TE64C-120-PV	2000004M	-60	3500	
SOLARAY	TE64C-80-1	1993001H	-60	3400	
SOLARAY	TE64C-80-2	1996001F	-60	3300	
SOLARAY	TE64C-80-2-PV	2000003B	-60	3500	
SOLARAY	TE64C-80-PV	2000004B	-60	3500	
SOLARAY	TE64P-120-1	1993001P	-60	3300	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
SOLARAY	TE64P-120-2	1996001N	-60	3300	
SOLARAY	TE64P-120-2-PV	2000003L	-60	3400	
SOLARAY	TE64P-80-1	1993001G	-60	3300	
SOLARAY	TE64P-80-2	1996001E	-60	3300	
SOLARAY	TE64P-80-2-PV	2000003E	-60	3400	
SOLARAY	TE80C-120-1	1993001S	-60	3400	
SOLARAY	TE80C-120-2	1996001Q	-60	3400	
SOLARAY	TE80C-120-2-PV	2000003O	-60	3500	
SOLARAY	TE80C-120-PV	2000004O	-60	3600	
SOLARAY	TE80P-120-1	1993001R	-60	3400	
SOLARAY	TE80P-120-2	1996001P	-60	3400	
SOLARAY	TE80P-120-2-PV	2000003N	-60	3500	
SOLARAY	TE80P-120-PV	2000004N	-60	3500	
SunSaver	NF40P-80S	1995010M	41	3100	
SunSaver	NF40P-80T	1995009M	41	3100	
SunSiphon	EPGX116-63-2	2001004I	15	3200	
SunSiphon	EPGX116-64-2	2001004J	15	3200	
SunSiphon	EPGX116-80-2	2001004L	15	3300	
SunSiphon	EPGX48-21-2	2001004A	15	1700	
SunSiphon	EPGX48-24-2	2001004B	15	1900	
SunSiphon	EPGX48-32-2	2001004C	15	2300	
SunSiphon	EPGX80-40-2	2001004D	15	2700	
SunSiphon	EPGX80-42-2	2001004E	15	2700	
SunSiphon	EPGX80-48-2	2001004F	15	2900	
SunSiphon	EPGX80-63-2	2001004G	15	3100	
SunSiphon	EPGX80-64-2	2001004H	15	3100	
SunSource	HX40P-80	1995001E	-28	3100	
SunSource	HX64P-120	1995001K	-28	3400	

Synergy Solar

Drainback Stainless HX	107-2T	2004005D	-50	3300	
Drainback Stainless HX	133-2T	2004005F	-50	3300	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
 SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Drainback Stainless HX	40-1T	2006019A	-50	2500	
Drainback Stainless HX	53-1T	2006019B	-50	2800	
Drainback Stainless HX	53-2T	2004005B	-50	2800	
Drainback Stainless HX	60-2T	2004005A	-50	2900	
Drainback Stainless HX	80-2T	2004005C	-50	3100	
Drainback Stainless HX	S53-2T	2004005E	-50	2600	

Thermal Conversion Technology, Inc. (TCT Solar)

ProgressivTube®	PT-30-CN	1995002A	10	2000	
ProgressivTube®	PT-35-CN	1995002B	10	2000	
ProgressivTube®	PT-40-CN	1995002C	10	2400	
ProgressivTube®	PT-50-CN	1995002D	10	2500	

Thermomax Industries Ltd.

Thermomax Mazdon	Mazdon 30-R120	2001029H	-60	2900	
Thermomax Mazdon	Mazdon 30-R80	2001029A	-60	2900	
Thermomax Mazdon	Mazdon 40-R120	2001029I	-60	3200	
Thermomax Mazdon	Mazdon 40-R80	2001029B	-60	3200	
Thermomax Mazdon	Mazdon 50-R120	2001029J	-60	3300	
Thermomax Mazdon	Mazdon 50-R80	2001029C	-60	3300	
Thermomax Mazdon	Mazdon 60-R120	2001029K	-60	3300	
Thermomax Mazdon	Mazdon 60-R80	2001029D	-60	3300	
Thermomax Mazdon	Mazdon 70-R120	2001029L	-60	3400	
Thermomax Mazdon	Mazdon 70-R80	2001029E	-60	3400	
Thermomax Mazdon	Mazdon 80-R120	2001029M	-60	3400	
Thermomax Mazdon	Mazdon 80-R80	2001029F	-60	3400	
Thermomax Mazdon	Mazdon 90-R120	2001029N	-60	3400	
Thermomax Mazdon	Mazdon 90-R80	2001029G	-60	3400	
Thermomax Solamax	Solamax 20R-R120	2004001I	-50	2200	
Thermomax Solamax	Solamax 20R-R80	2004001A	-50	2300	
Thermomax Solamax	Solamax 20W	2004002A	-50	2300	
Thermomax Solamax	Solamax 30R-R120	2004001J	-50	2800	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (kWhr)	Comments
Thermomax Solamax	Solamax 30R-R80	2004001B	-50	2900	
Thermomax Solamax	Solamax 30W	2004002B	-50	2700	
Thermomax Solamax	Solamax 40R-R120	2004001K	-50	3100	
Thermomax Solamax	Solamax 40R-R80	2004001C	-50	3100	
Thermomax Solamax	Solamax 40W	2004002C	-50	3100	
Thermomax Solamax	Solamax 50R-R120	2004001L	-50	3200	
Thermomax Solamax	Solamax 50R-R80	2004001D	-50	3200	
Thermomax Solamax	Solamax 60R-R120	2004001M	-50	3300	
Thermomax Solamax	Solamax 60R-R80	2004001E	-50	3300	
Thermomax Solamax	Solamax 70R-R120	2004001N	-50	3300	
Thermomax Solamax	Solamax 70R-R80	2004001F	-50	3300	
Thermomax Solamax	Solamax 80R-R120	2004001O	-50	3400	
Thermomax Solamax	Solamax 80R-R80	2004001G	-50	3400	
Thermomax Solamax	Solamax 90R-R120	2004001P	-50	3400	
Thermomax Solamax	Solamax 90R-R80	2004001H	-50	3400	

TrendSetter Solar Products, Inc.

Six Rivers Solar	TS-DB-112-2EP40FP-Elec	2001007A	-20	2700	
Six Rivers Solar	TS-DB-199-3EP40FP-Elec	2001007B	-20	2800	
Six Rivers Solar	TS-DB-199-4EP40FP-Elec	2001007C	-20	2900	
Six Rivers Solar	TS-DB-299-5EP40FP-Elec	2001007D	-20	2900	
Six Rivers Solar	TS-DB-299-6EP40FP-Elec	2001007E	-20	2900	

VELUX America Inc.

VELUX	CLI-U12 SKO W/L 218 AUX EL	2008021A	-40	3300	
VELUX	CLI-U12 SKO W/L 218 EL B/U	2008020A	-40	3300	
VELUX	CLI-U12 SKO W/L 318 AUX EL	2008021B	-40	3400	
VELUX	CLI-U12 SKO W/L 318 EL B/U	2008020B	-40	3400	

*** A conventional 50 gallon electric water heater would consume 3600 kWh under these rating conditions.**

Prepared for Tucson, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

Solar Rating and Certification Corporation
Estimated Annual Performance of OG-300 Certified Solar Water Heating Systems
Tucson, Arizona
with Gas Backup

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
ACR Solar International					
Skyline System 3	200132C502TG	2001018B	30	125	
Skyline System 3	200132C50T20G	2002005A	20	105	
Skyline System 5	200152C80EX2TG	2001019A	-54	110	
Skyline System 5	200153C80EX2TG	2001019B	-54	135	
BTF, Ltd.					
Solar Patriot™	SP20-1-65G-DT-G	2007001A	-50	105	
Solar Patriot™	SP20-2-80G-DT-G	2007001B	-50	160	
Butler Sun Solutions					
Solar Butler	BSS-PV1-40Ga	2005006A	-54	120	
Solar Butler	BSS-PV1-40Gb	2005006B	-54	100	
Solar Butler	BSS-PV1-40Gc	2005006I	-54	135	
Solar Butler	BSS-PV1-40Gd	2005006K	-54	140	
Solar Butler	BSS-PV1-50Ga	2005006C	-54	140	
Solar Butler	BSS-PV1-50Gb	2005006J	-54	145	
Solar Butler	BSS-PV1-50Gc	2005006H	-54	135	
Solar Butler	BSS-PV1-80G2a	2005010A	-54	105	
Solar Butler	BSS-PV1-80G2b	2005010B	-54	120	
Solar Butler	BSS-PV1-80Ga	2005006E	-54	155	
Solar Butler	BSS-PV1-80Gc	2005006G	-54	140	
Solar Butler	BSS-S1-40Ga	2003016A	-54	60	
Solar Butler	BSS-S1-40Gb	2003016B	-54	45	
Solar Butler	BSS-S1-40Gc	2003016I	-54	70	
Solar Butler	BSS-S1-50Ga	2003016C	-54	75	
Solar Butler	BSS-S1-50Gc	2003016H	-54	75	
Solar Butler	BSS-S1-80G2a	2005009A	-54	105	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
Solar Butler	BSS-S1-80G2b	2005009B	-54	120	
Solar Butler	BSS-S1-80Ga	2003016E	-54	90	
Solar Butler	BSS-S1-80Gc	2003016G	-54	75	

Davis Energy Group

SunCache	SCG-100-GS	2008009B	20	75	
SunCache	SCG-100-GTL	2008010B	20	110	
SunCache	SCG-50-GS	2008009A	20	65	
SunCache	SCG-50-GTL	2008010A	20	105	
SunCache	SCU-50-GS	2008007A	20	45	
SunCache	SCU-50-GTL	2008008A	20	85	

Enerworks, Inc.

Solar Water Heating Appliance	EWRA1-G40	2006004A	-50	120	
Solar Water Heating Appliance	EWRA1-G80	2006004B	-50	125	
Solar Water Heating Appliance	EWRA2-G100	2006004D	-50	150	
Solar Water Heating Appliance	EWRA2-G80	2006004C	-50	145	
Solar Water Heating Appliance	EWRA3-G100	2006004E	-50	140	
Solar Water Heating Appliance	EWRA3-G120	2006004F	-50	145	
Solar Water Heating Appliance	EWRA4-G120	2006004G	-50	140	
Solar Water Heating Appliance	EWRA4-G144	2006004H	-50	135	

Fafco, Inc.

Polymer Drainback	VDB-48U-50G-50S	2007004A	-20	90	
Polymer Drainback	VDB-48U-50G-80S	2007004B	-20	100	
Polymer Drainback	VDB-48UX2-50G-50S	2007004C	-20	105	
Polymer Drainback	VDB-48UX2-50G-80S	2007004D	-20	115	

Heat Transfer Products

Phoenix Solar	PH-119S	2007023B	-60	175	
Phoenix Solar	PH-80S	2007023A	-60	150	
SuperStor Contender Solar	SSC-119SB	2007012C	-60	175	
SuperStor Contender Solar	SSC-50SB	2007012A	-60	155	
SuperStor Contender Solar	SSC-80SB	2007012B	-60	165	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
SuperStor Ultra Solar	SSU-119SB	2007021C	-60	175	
SuperStor Ultra Solar	SSU-119SB-DW	2007022B	-60	175	
SuperStor Ultra Solar	SSU-60SB	2007021A	-60	155	
SuperStor Ultra Solar	SSU-80SB	2007021B	-60	165	
SuperStor Ultra Solar	SSU-80SB-DW	2007022A	-60	165	

Heliodyne, Inc.

Helio-Flo	HF 13366 G 50 AC D Z	2001025A	27	125	
Helio-Flo	HF 1408 G 50 AC D Z	2001025B	27	140	
Helio-Flo	HF 1410 G 80 AC D Z	2001025C	27	160	
Helio-Flo	HF 23366 G 80 AC D Z	2001025D	27	175	
Helio-Flo	HF 2408 G 120 AC D Z	2001025F	27	180	
Helio-Flo	HF 2408 G 80 AC D Z	2001025E	27	175	
Helio-Flo	HF 2410 G 120 AC D Z	2001025G	27	185	
Helio-Flo	HF 3408 G 120 AC D Z	2001025H	27	180	
Helio-Flo	HF 3410 G 120 AC D Z	2001025I	27	180	
Heliopak	16 DWCL HP 1 3366 G 80 ACD Z	1998001G	-60	110	
Heliopak	16 DWCL HP 1 408 G 65 ACD Z	1998001F	-60	115	
Heliopak	16 DWCL HP 1 408 G 65 PVD Z	1998002C	-60	125	
Heliopak	16 DWCL HP 1 408 G 80 ACD Z	1998001I	-60	115	
Heliopak	16 DWCL HP 1 410 G 65 ACD Z	1998001A	-60	125	
Heliopak	16 DWCL HP 1 410 G 80 ACD Z	1998001J	-60	125	
Heliopak	16 DWCL HP 1 410 G 80 PVD Z	1998002A	-60	135	
Heliopak	16 DWCL HP 2 3366 G 80 ACD Z	1998001H	-60	130	
Heliopak	16 DWCL HP 2 408 G 120 ACD Z	1998001C	-60	130	
Heliopak	16 DWCL HP 2 408 G 80 ACD Z	1998001B	-60	130	
Heliopak	16 DWCL HP 2 410 G 120 ACD Z	1998001D	-60	135	
Helio-Pak Helix SS PV	HP HX SS 1 3366 G PV 50 EE D Z	2005004A	-60	120	
Helio-Pak Helix SS PV	HP HX SS 1 408 G PV 50 EE D Z	2005004B	-60	125	
Helio-Pak Helix SS PV	HP HX SS 1 410 G PV 80 EE D Z	2005004C	-60	135	
Helio-Pak Helix SS PV	HP HX SS 2 3366 G PV 80 EE D Z	2005004D	-60	140	
Helio-Pak Helix SS PV	HP HX SS 2 408 G PV 80 EE D Z	2005004E	-60	140	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
Helio-Pak Helix SS PV	HP HX SS 2 410 G PV 120 SE D Z	2005004F	-60	145	
Integrated Solar, LLC					
CopperSun	CS330-G	1999001B	20	70	
CopperSun	CS330SV-G	2002008A	20	70	
CopperSun	CS340-G	1999001C	20	75	
CopperSun	CS340SV-G	2002008B	20	70	
CopperSun	CS440-G	1999001A	20	80	
CopperSun	CS450-G	1999001D	20	85	
Radco Drainback Heat Exchanger	R-DBHX-12-120-GD-80P	1998004C	-60	155	
Radco Drainback Heat Exchanger	R-DBHX-8-65-GD-40P	1998004A	-60	120	
Radco Drainback Heat Exchanger	R-DBHX-8-80-GD-64P	1998004B	-60	145	
Mr. Sun Solar					
Sol-Reliant	SR 40/80 G PVDB	2004009B	-50	150	
Sol-Reliant	SR 56/80 G PVDB	2004009A	-50	170	
Sol-Reliant	SR112/120 G PVDB	2007026C	-50	185	
Sol-Reliant	SR112/80 G PVDB	2007026B	-50	185	
Sol-Reliant	SR80/80 G PVDB	2007026A	-50	180	
Oventrop Corporation					
OVSOL System 5	OV-5 Regusol Indirect	2007017A	-20	80	
Schuco USA L.P.					
Premium Package	Premium II-80G	2006011A	-40	125	
Premium Package	Premium III-120G	2006011B	-40	135	
Slimline Package	Slimline II-80G	2006013A	-40	125	
Slimline Package	Slimline III-120G	2006013B	-40	130	
Solahart Industries					
SOLAHART	ASG 181BCXII	2001017B	19	100	
SOLAHART	ASG 181J & ASG 181J Free Heat	2001016A	19	95	
SOLAHART	ASG 181KF & ASG 181KF Free He	2001017A	19	100	
SOLAHART	ASG 181L	2001015A	41	85	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
SOLAHART	ASG 182BCXII	2001017D	19	140	
SOLAHART	ASG 182J & ASG 182J Free Heat	2001016B	19	125	
SOLAHART	ASG 182KF & ASG 182KF Free He	2001017C	19	140	
SOLAHART	ASG 302BCXII	2001017F	19	140	
SOLAHART	ASG 302J & ASG 302J Free Heat	2001016C	19	130	
SOLAHART	ASG 302JXII	2001016D	19	130	
SOLAHART	ASG 302KF & ASG 302KF Free He	2001017E	19	140	
SOLAHART	ASG 302L	2001015B	41	120	
SOLAHART	ASG 303BCXII	2001017H	19	160	
SOLAHART	ASG 303J & ASG 302J Free Heat	2001016E	19	145	
SOLAHART	ASG 303JXII	2001016F	19	145	
SOLAHART	ASG 303KF & ASG 303KF Free He	2001017G	19	160	
SOLAHART	ASG 303L	2001015C	41	140	
SOLAHART	ASG 443BCXII	2001017J	19	160	
SOLAHART	ASG 443J & ASG 443J Free Heat	2001016G	19	145	
SOLAHART	ASG 443JXII	2001016H	19	145	
SOLAHART	ASG 443KF & ASG 443KF Free He	2001017I	19	160	
SOLAHART	ASG 443L	2001015D	41	140	
SOLAHART	ASG 444BCXII	2001017L	19	165	
SOLAHART	ASG 444J & ASG 444J Free Heat	2001016I	19	150	
SOLAHART	ASG 444JXII	2001016J	19	150	
SOLAHART	ASG 444KF & ASG 444KF Free He	2001017K	19	165	
SOLAHART	ASG 444L	2001015E	41	145	

Solene

Solene/Chromagen DC Closed Lo	SLCR32DC-80HE-XG	2006027A	-10	110	
Solene/Chromagen DC Closed Lo	SLCR40DC-80HE-XG	2006027B	-10	120	
Solene/Chromagen DC Closed Lo	SLCR64DC-120HE-XG	2006027E	-10	130	
Solene/Chromagen DC Closed Lo	SLCR64DC-80HE-XG	2006027C	-10	130	
Solene/Chromagen DC Closed Lo	SLCR80DC-120HE-XG	2006027F	-10	135	
Solene/Chromagen DC Closed Lo	SLCR80DC-80HE-XG	2006027D	-10	135	
Solene/Chromagen Drain Back	SLCR32DC-80DB-XG	2006026A	-10	105	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
Solene/Chromagen Drain Back	SLCR40DC-80DB-XG	2006026B	-10	115	
Solene/Chromagen Drain Back	SLCR64DC-120DB-XG	2006026E	-10	130	
Solene/Chromagen Drain Back	SLCR64DC-80DB-XG	2006026C	-10	130	
Solene/Chromagen Drain Back	SLCR80DC-120DB-XG	2006026F	-10	130	
Solene/Chromagen Drain Back	SLCR80DC-80DB-XG	2006026D	-10	130	
Solene/Corona DC Closed Loop	SLCO32DC-80HE-XG	2006025A	-10	110	
Solene/Corona DC Closed Loop	SLCO40DC-80HE-XG	2006025B	-10	120	
Solene/Corona DC Closed Loop	SLCO64DC-120HE-XG	2006025E	-10	130	
Solene/Corona DC Closed Loop	SLCO64DC-80HE-XG	2006025C	-10	130	
Solene/Corona DC Closed Loop	SLCO80DC-120HE-XG	2006025F	-10	135	
Solene/Corona DC Closed Loop	SLCO80DC-80HE-XG	2006025D	-10	135	
Solene/Corona DC Open Loop	SLCO32DC-80-XG	2007016A	32	125	
Solene/Corona DC Open Loop	SLCO40DC-80-XG	2007016B	32	130	
Solene/Corona DC Open Loop	SLCO64DC-80-XG	2007016C	32	135	
Solene/Corona DC Open Loop	SLCO80DC-80-XG	2007016D	32	140	
Solene/Corona Drainback	SLCO32DC-80DB-XG	2006024A	-10	105	
Solene/Corona Drainback	SLCO40DC-80DB-XG	2006024B	-10	115	
Solene/Corona Drainback	SLCO64DC-120DB-XG	2006024E	-10	125	
Solene/Corona Drainback	SLCO64DC-80DB-XG	2006024C	-10	130	
Solene/Corona Drainback	SLCO80DC-120DB-XG	2006024F	-10	130	
Solene/Corona Drainback	SLCO80DC-80DB-XG	2006024D	-10	130	

SunEarth, Inc.

Cascade	ECRD-40-80-2G	2001028B	-50	135	
Cascade	ECRD-48-80-2G	2001028F	-50	145	
Cascade	ECRD-64-80-2G	2001028H	-50	160	
Cascade	EPRD-40-80-2G	2001028A	-50	130	
Cascade	EPRD-42-80-2G	2001028C	-50	130	
Cascade	EPRD-48-80-2G	2001028E	-50	140	
Cascade	EPRD-64-80-100G	2001028J	-50	135	
Cascade	EPRD-64-80-2G	2001028G	-50	155	
Cascade	EPRD-64-80-75G	2001028I	-50	140	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
CopperHeart	CP-20G	2001002A	20	65	
CopperHeart	CP-20-TLG	2002006A	20	95	
CopperHeart	CP-30G	2001002B	20	90	
CopperHeart	CP-30-TLG	2002006B	20	115	
CopperHeart	CP-40G	2001002C	20	100	
CopperHeart	CP-40-TLG	2002006C	20	125	
CopperHeart	CP-60PG	2001002D	20	115	
CopperHeart	CP-80PG	2001002E	20	125	
SOLARAY	TE40C-80-2G	2001001B	-60	150	
SOLARAY	TE40C-80-2G-PV	2001003B	-60	145	
SOLARAY	TE40P-80-2G	2001001A	-60	145	
SOLARAY	TE40P-80-2G-PV	2001003A	-60	135	
SOLARAY	TE48C-80-2G	2001001D	-60	155	
SOLARAY	TE48C-80-2G-PV	2001003D	-60	155	
SOLARAY	TE48P-80-2G	2001001C	-60	155	
SOLARAY	TE48P-80-2G-PV	2001003C	-60	150	
SOLARAY	TE48P-80-75G	2001001G	-60	125	
SOLARAY	TE63P-120-2G	2008013A	-60	180	
SOLARAY	TE64C-80-2G	2001001F	-60	170	
SOLARAY	TE64C-80-2G-PV	2001003F	-60	170	
SOLARAY	TE64P-80-2G	2001001E	-60	165	
SOLARAY	TE64P-80-2G-PV	2001003E	-60	170	
SunSiphon	EPGX116-63-2G	2001005I	15	150	
SunSiphon	EPGX116-64-2G	2001005J	15	155	
SunSiphon	EPGX116-80-2G	2001005L	15	165	
SunSiphon	EPGX48-21-2G	2001005A	15	75	
SunSiphon	EPGX48-24-2G	2001005B	15	85	
SunSiphon	EPGX48-32-2G	2001005C	15	100	
SunSiphon	EPGX80-40-2G	2001005D	15	120	
SunSiphon	EPGX80-42-2G	2001005E	15	125	
SunSiphon	EPGX80-48-2G	2001005F	15	135	
SunSiphon	EPGX80-63-2G	2001005G	15	150	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
SunSiphon	EPGX80-64-2G	2001005H	15	150	

Thermal Conversion Technology, Inc. (TCT Solar)

ProgressivTube®	PT-40-CN2-GX100	1999002A	10	135	
ProgressivTube®	PT-20-CN-TL	2008015B	10	100	
ProgressivTube®	PT-30-CN-G	1998006A	10	95	
ProgressivTube®	PT-30-CN-TL	2008015A	10	145	
ProgressivTube®	PT-35-CN-G	1998006B	10	95	
ProgressivTube®	PT-40-CN2-GX75	1998007A	10	125	
ProgressivTube®	PT-40-CN-G	1998006C	10	110	
ProgressivTube®	PT-40-CN-GX	1998006E	10	115	
ProgressivTube®	PT-40-CN-TL	2008015C	10	165	
ProgressivTube®	PT-50-CN-G	1998006D	10	115	
ProgressivTube®	PT-50-CN-GX	1998006F	10	115	
ProgressivTube®	PT-50-CN-TL	2008015D	10	165	

TrendSetter Solar Products, Inc.

Six Rivers Solar	SRS-100-2-32-PC	2001006H	-20	125	
Six Rivers Solar	SRS-150-2-40-PC	2001006J	-20	175	
Six Rivers Solar	SRS-150-3-32-PC	2001006K	-20	180	
Six Rivers Solar	TS-100-1-30-PC	2005002A	-20	160	
Six Rivers Solar	TS-150-2-22-PC	2005002B	-20	175	
Six Rivers Solar	TS-200-3-30-PC	2005002C	-20	185	
Six Rivers Solar	TS-200-4-30-PC	2005002D	-20	185	
Six Rivers Solar	TS-300-5-30-PC	2005002E	-20	185	
Six Rivers Solar	TS-300-6-30-PC	2005002F	-20	185	
Six Rivers Solar	TS-DB-112-2EP40FP-CNG/P	2001006A	-20	125	
Six Rivers Solar	TS-DB-199-3EP40FP-CNG/P	2001006B	-20	135	
Six Rivers Solar	TS-DB-199-4EP40FP-CNG/P	2001006C	-20	140	
Six Rivers Solar	TS-DB-299-5EP40FP-CNG/P	2001006D	-20	140	
Six Rivers Solar	TS-DB-299-6EP40FP-CNG/P	2001006E	-20	140	
Six Rivers Solar	TS-DB-52-1EP32FP-CNG/P	2001006F	-20	95	
Six Rivers Solar	TS-DB-52-1EP40FP-CNG/P	2001006G	-20	100	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
 c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010

System Name	System Model	System Number	FTL (°F)	Energy Savings* (Therms)	Comments
Six Rivers Solar	TS-DB-72-1EP40FP-Elec	2001006I	-20	150	
VELUX America Inc.					
VELUX	CLI-U12 SKO W/L 218 AUX GAS	2008022A	-40	170	
VELUX	CLI-U12 SKO W/L 318 AUX GAS	2008022B	-40	180	

*** A conventional 50 gallon gas water heater would consume 185 therms under these rating conditions.**

Prepared for Tuscon, Arizona by:
SOLAR RATING & CERTIFICATION CORPORATION
c/o FSEC ♦ 1679 Clearlake Road ♦ Cocoa, FL 32922 ♦ (321) 638-1537 ♦ Fax (321) 638-1010